

# SONY PDW-U1

## Technical Specifications



<b>Video file format:</b>	MPEG HD422 (CBR, 50 Mbps) MPEG HD: - HQ mode (VBR, maximum bit rate: 35 Mbps), - SP mode (CBR, 25 Mbps), - LP mode (VBR, maximum bit rate: 18 Mbps), MPEG IMX (CBR, 50/40/30 Mbps) DVCAM (CBR, 25 Mbps)
<b>Audio file format:</b>	MPEG HD422: 8 ch/24 bits/48kHz, MPEG HD: 4/2 ch/16bits/48kHz, MPEG IMX: 8 ch/16 bits/48 kHz, or 4 ch/24 bits/48 kHz, DVCAM: 4 ch/16 bits/48 kHz
<b>Media type:</b>	Professional Disc Drive
<b>Supported media:</b>	PFD23AX – HD422: 43 min. / XAVC HD: 21 min. – 23 GB PFD50DLAX – HD422: 95 min. / XAVC HD: 46 min. – 50 GB
<b>Input / Output:</b>	Hi-Speed-USB (USB 2.0) (1 x)
<b>Input power:</b>	10 W
<b>Weight:</b>	1,4 kg
<b>Dimensions (B x H x T):</b>	86 mm x 130 mm x 189 mm

# SONY PDW-U2

## Technical Specifications



<b>Video file format:</b>	MPEG HD422 (50 Mb/s) MPEG HD (35/25/18 Mb/s) MPEG IMX (50/40/30 Mb/s) DVCAM (25 Mb/s) Proxy Video: MPEG-4
<b>Audio file format:</b>	MPEG HD422: 8 ch/24 bits/48 kHz MPEG HD: 4/2 ch/16bits/48kHz MPEG IMX: 8 ch/16 bits/48 kHz, or 4 ch/24 bits/48 kHz DVCAM: 4 ch/16 bits/48 kHz
<b>Media type:</b>	Professional Disc Drive
<b>Supported media:</b>	PFD23AX – HD422: 43 min. / XAVC HD: 21 min. – 23 GB PFD50DLAX – HD422: 95 min. / XAVC HD: 46 min. – 50 GB
<b>Input / Output:</b>	Super Speed USB (USB 3.0) (1 x)
<b>Input power:</b>	19 W
<b>Weight:</b>	1,7 kg
<b>Dimensions (B x H x T):</b>	67,4 x 164 x 219 mm (without protruding parts)

# SONY SXS

## Technical Specifications



### SBAC-US30 - Read / Write Device

Connection:	SuperSpeed USB (USB3.0)
Power supply:	USB
Power input:	4,5 W
Dimensions:	Ca. 99 × 31 × 132 mm

### SXS Pro Plus Memory Card

Interface:	ExpressCard/34, PCI Express - 2nd generation interface
Read speed:	3,5 GB/s (440 Mbit/s)
Write speed:	3,2 GB/s (400 Mbit/s)
Minimal write speed:	1,3 GB/s
Capacity:	64 GB: SBP-64E 128 GB: SBP-128E 256GB: SBP-256E
Weight:	ca. 27 g
Dimensions:	ca. 34 x 5 x 75 mm (without protruding parts)